

# JCM 200 U

Magnetic Base Drills up to 2 in (50 mm)

Order number:: 7 270 44 61 12 0



Universal with 2-speed gearbox and outstanding functionality for flexible operation in the workshop and on the construction site.

- Compact with high functionality for universal use on the construction site and in the workshop.
- Simple and error-proof control concept in the operator's field of view.
- Double drill motor guides enable use of the largest core bits.
- Reversible
- Electronic speed control.
- Slugger high-power motor with stable speed.
- High magnetic holding force.
- Convenient magnetic holding force gauge.
- Integrated cooling tank.
- Hand feed wheel can be mounted on either side.
- MK3 interface.
- Optional Weldon QuickIN arbor is available. (uses standard 3/4 in Weldon shank cutters).



# JCM 200 U

Magnetic Base Drills up to 2 in (50 mm)

Order number:: 7 270 44 61 12 0

## Technical data

Carbide annular cutter max. dia.	2 in
HSS annular cutters max. dia.	1 9/16 in
Mag base, max. drilling depth	2 in
Twist drill max. dia.	7/8 mm
Tapping	1/2 in
Max. countersinking dia.	2 in
Reaming max. dia.	7/8 in
Power consumption	1,200 Watts
Power output	610 Watts
1st gear	130-260 rpm
2nd gear	260-520 rpm
Annular cutter holder	QuickIN
Tool mount	MT 3
Stroke	5 11/16 in
Magnetic holding force	2,750 lbs
Magnetic base dimensions	7 11/16 x 3 9/16 in
Cable with plug	13 ft
Weight according to EPTA	30.6 lbs
Corded	X

## Price includes:

1 case
1 coolant tank
1 safety strap
1 chip hook
1 pilot pin 4 1/8 in (105 mm)
1 touch guard
1 drift