

ELITE110

Superior 4 Station Ironworker

Universal Open Tooling Station
ANSI B11.5-1988R(02) Compliant
ETL/UL Approved Controls



ELITE Integrated Features:

Hydraulic Hold-Down
E-Stop/Lockout-Tagout
Electric Stroke Control
Hydraulic Accessory Pack
Central Lubrication System

Swing-Away Stripper Assembly
Roller Encoder Measuring System
Quick Change Punch Assembly
Premium Gauging Tables
LED Lighting

PUNCH

Rating: 110 Tons
Max. Capacity: 1-3/8" Dia. in 1" A36
Stroke: 1-13/16"
Throat Depth: 11-3/4"
Open Height: 8-5/8"
Shut Height: 6-13/16"
Work Height: 41"

OPTIONAL COPER NOTCHER

Max. Capacity: 2-1/2" x 6" x 1/2"
Work Height: 44-3/16"

GENERAL SPECIFICATIONS

Standard Motor: 7.5 HP 3~ 208 V or 230 V
1765 RPM 22 A
Optional Motors: 7.5 HP 3~ 460 V
1765 RPM 11 A
7.5 HP 3~ 575 V
1770 RPM 8 A
7.5 HP 1~ 230 V
1765 RPM 36 A
Hydraulic Pump: 10-1/2 GPM - 2 Stage
Valve Pressure: 3000 PSI
Reservoir: 17 Gallons
Cylinder: 3-1/2" Ram

FLAT BAR SHEAR

Max. Capacity: 3/4" x 14"
1" x 12"
Max. Round: 1-1/4"
Max. Square: 1-1/4"
Work Height: 41-1/2"

ANGLE SHEAR

Max. Capacity: 6" x 6" x 1/2"
Work Height: 50-7/8"

OPEN STATION

Throat Depth: 15-1/2"
Open Height: 8-5/8"
Shut Height: 6-13/16"
Stroke: 1-13/16"
Work Height: 39-3/16"

DIMENSIONS

Height: 66-1/16"
Width: 57-1/4"
Depth: 42-3/8"
Shipping Weight: 5380 lb



Shown with optional Brake

EDWARDSIRONWORKERS.COM

(800) 373-8206