

## **JCM 256 U**

Mag Drill unit up to 2-1/2 [65] in[mm]

Order number:: 7 270 47 61 12 0



High-performance with 2-speed gearbox and outstanding functionality for universal and efficient use in the workshop.

- Stable speed, even in the toughest applications.
- Fine drill spindle adjustment for convenient machine alignment.
- Double drill motor guides enable use of the largest core bits.
- Optional Weldon QuickIN arbor is available. (uses standard 3/4 in Weldon shank cutters).
- Reversible
- Electronic speed control.
- MK3 interface.
- High magnetic holding force.
- Convenient magnetic holding force gauge.
- Integrated cooling tank.



## **JCM 256 U**

Mag Drill unit up to 2-1/2 [65] in[mm]

Order number:: 7 270 47 61 12 0

## Technical data

Carbide annular cutter max. dia.	2 9/16 In
HSS annular cutters max. dia.	1 3/4 ln
Mag base, max. drilling depth	2 In
Twist drill max. dia.	1 mm
Tapping	5/8 In
Max. countersinking dia.	2 In
Reaming max. dia.	1 In
Power consumption	1,300 Watts
Power output	730 Watts
Load speed: 1st gear	120-240 rpm
Load speed: 2nd gear	260-520 rpm
Annular cutter holder	QuickIN
Tool mount	MT 3
Stroke	5 11/16 In
Adjustment range	± 6 mm
Drill stand angular adjustment	± 7°
Magnetic holding force	3,080 lbs
Magnetic base dimensions	8 1/16 x 3 3/4 In
Cable with plug	13 ft
Weight according to EPTA	35.5 lbs
Corded	Х

## Price includes:

1 case
1 coolant tank
1 safety strap
1 chip hook
1 pilot pin 4 1/8 in (105 mm)
1 touch guard
1 drift